

Primer

Triflex Glass Primer



Product information

Applications

Triflex Glass Primer is used as a primer on unpolished glass substrates under various Triflex systems.

Properties

1-component glass primer. Triflex Glass Primer has the following properties:

- Fast-drying
- Fast recoating time
- Low viscosity

Pack size

Single can

750 ml Triflex Glass Primer

Colours

Transparent

Storage

Can be stored unopened and unmixed for approx. 12 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.

Conditions for use

Triflex Glass Primer can be applied at substrate and ambient temperatures between 0 °C and +35 °C.

Preparation of the substrate

The substrate must be sound, dry and free of ice, loose particles, grease and oil. Substrate adhesion must be tested on a case-by-case basis.

Material consumption

Approx. 0.05 l/m² (50 ml) on a smooth, even surface



Drying time

Can be recoated after: approx. 15 min. at +20 °C

Can be recoated until: approx. 3 hrs. at +20 °C

Notes on special hazards

See Safety Data Sheet, section 2

Safety tips

See Safety Data Sheet, sections 7 and 8

Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

General notes

We guarantee the consistently high quality of our products. Non-system substances must not be added to Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for the respective purpose. Technical information is subject to changes without notice in the interests of technical advancement or enhancement of our products.

Important note:

Special under-gloves must be worn when applying Triflex Glass Primer.