

DECLARATION OF PERFORMANCE
as per Annex III of Regulation (EU) no. 305/2011
amended by delegated Regulation (EU) no. 574/2014

for the product Triflex ProThan / Triflex ProThan Detail

No. 25580_25560_1

Unique identity code for product type: .

No. 25580_25560_1

Designated use:

Two component polyurethane-based roof waterproofing with polyester fleece reinforcement insert,
applied in liquid form

Manufacturer:

Triflex GmbH & Co KG
Karlstraße 59
32423 Minden
Deutschland

System for assessment and testing of performance constancy:

System 3

European assessment document:

ETAG 005: 2005-06, Part 6

European Technical Approval:

ETA-10/0254 of 22.06.2018

Technical assessment body:

DIBt

Notified bodies:

Materialprüfungsamt Nordrhein-Westfalen (MPA NRW), Nr. 0432

Declared performances:

The ETAG 005 kit polyurethane-based roof waterproofing, applied in liquid form, comprises the following components:

- Roof waterproofing, applied in liquid form, made of Triflex ProThan / Triflex ProThan Detail
- Polyester fleece Triflex Special Fleece / Triflex Special Fleece SK / Triflex Special Fleece inside corner / Triflex Special Fleece outside corner / Triflex Special Fleece pipe as insert
- further components Triflex Pox R 100 / Triflex Glass Primer

Essential characteristics	Performance	AVCP-System	Harmonised technical specification
Minimum layer thickness	2,1 mm	System 3	ETAG 005: 2005-06
Minimum consumption	3,0 kg/m ²		
Service life	W 3		
Climate zones	M & S		
Payloads	P1-P4		
Roof pitch	S1-S4		
Lowest surface temperature	TL4		
Highest surface temperature	TH4		
Resistance to flying sparks EN 13501-5	B _{roof} (t1), (t4)		
Fire classification EN 13501-1	E		
Water vapour diffusion resistance	μ ~ 35000		
Impermeability to water	Passed		
Statement on hazardous substances	None included		
Resistance to root penetration	NPD		
Resistance to wind loads	> 50 kPa		
Slip resistance	NPD		

The prerequisites for the declared performance are the layer structure as defined in ETA - 10/0254, the specified minimum layer thickness of 2,1 mm and a coating weight per unit area of at least 110 g/m².

The performance of the aforementioned product matches the declared performance. The above manufacturer is solely responsible for the issuing of the declaration of performance in accordance with Regulation (EU) no. 305/2011.

Signed on behalf of the manufacturer and in the name of the manufacturer by:

i.V. Dipl.-Ing. Frank Becker, Head of Technology

Minden, 17.05.2019

i.V. F. Becker
.....
(Signature)