

From the liquid applied waterproofing specialist The number 1 for details.

## Triflex ProDetail<sup>®</sup>

Triflex

ProDetail

8

# Triflex

Abdichtung | Waterproofing | Étanchéité

ProDeta

Afdichting | Impermeabilizzatione

### Triflex ProDetail Often copied. But never matched.

Tried and tested on building sites over 40 years, adhesion to over 1,400 tested substrates, countless areas of application, exceptionally reliable, extremely durable and waterproof to the smallest detail: it's no coincidence that Triflex ProDetail is the number 1 waterproofing solution. With unparalleled versatility, Triflex ProDetail is the from skylights on roofs, gullies on balconies, balustrade posts on stairs, joints on parking decks through to permanently elastic joints on cable car stations and joint details on milking plants. Triflex ProDetail is more than just a waterproofing product – with our training and service and your application expertise, it is the best possible

Triflex ProDetail's strengths

### From us. For you. Great advantages.

Fast-curing liquid applied waterproofing. Reduced time on site, fast project completion.

40 years experience on building sites, tried and tested on more than 1,400 substrates. Tailored advice and optimal waterproofing solutions.

Comprehensive range of additional products for optimal application. Problem-free adhesion even on special and demanding substrates.

Certified in the highest performance categories, approved in the application categories K1 and K2 as per DIN 18531. Effective, risk-free working, tried and tested solutions.

### Thoroughly impressive.



#### Unbeatably versatile.

New builds, refurbishments, minor repairs, wall junctions and door sills, gullies, ventilators, joints, beams, green areas, various substrates etc.: with Triflex ProDetail you have the ideal, customised and long-lasting solution for all waterproofing requirements



#### Extremely durable.

Triflex ProDetail is certified in the highest performance categories and has performed successfully in extensive tests and in long-term practical use. The expected service life in accordance with ETAG 005 is 25 years.



#### Extremely waterproof down to the smallest detail.

Joints, beams, joint details, structural movement where components meet and cracks: Triflex ProDetail comes into its own when handling complicated details. The flexible material together with the fleece reinforcement ensures seamless and jointless waterproofing.



Can be applied at temperatures down to -5 °C Additional revenue regardless of the weather conditions and time of year.

Resistant to weather, UV and hydrolysis. Long-lasting functional solutions which ensure great reliability.

Can be applied at substrate temperatures of up to +50 °C. All year round, maximum scope for installation.

## Coordinated, requirement-oriented, reliable Systematic waterproofing.

As your system provider, it is of the utmost importance to us that our products are perfectly coordinated. Triflex ProDetail combines fast-curing liquid applied waterproofing with full-surface fleece reinforcement. It is applied in a cold liquid form, wet-on-wet, and cures extremely rapidly to create a long-lasting and flexible finish.



With Triflex ProDetail you have complete peace of mind whatever the application. At Triflex, we regard continuous internal and external quality controls in production and extensive field tests prior to market launch as essential.

- Highest possible categories as per ETAG 005 (W3, M and S, P1-P4, S1-S4, TL4, TH4).
- Certified safety as per ETA, root- and rhizome-resistant as per FLL.
- Material guarantee filed with the Central Organisation of the German Roofing Trade Association (ZVDH).



With Triflex ProDetail even smaller jobs and repairs can be managed quickly and simply. You benefit from the fact that you only have to mix the amount which you actually require. To speed up the process even further: Simply order and we will deliver to the building site.

DIBE DIN EOTA

kiwa

**CSTB** 

### A selection of our additional products Anything is possible. Everything is watertight.

In most cases **Triflex ProDetail** can be used without a primer. For all other substrates we offer solutions which render time-consuming preliminary work superfluous and enable you to work more quickly and simply. Moreover, we also offer a wide range of products for the safe and reliable waterproofing of joints and complex details.

### Primers

### **Triflex Metal Primer**

#### **Metal substrates**

- + Alternative to protracted grinding
- Suitable for all metal surfaces, e.g., copper and stainless steel
- + Also for rusty substrates
- Fast drying and fast recoat time



### Complementary products

### Triflex ProFibre

### Highly complex details

- Simple application even with hard-to-reach details where fleece sections cannot be used
- Fibre-reinforced, elastic waterproofing



### **Triflex Primer 610**

### FPO and EPDM membranes

- + Universal, quick-drying and optimised adhesion
- Can be recoated after 30 minutes
- 1-component, low volume



### Triflex Special Fleece SK

### **Vertical joints**

- Self-adhesive fleece polyester
- Material-strengthening and
- crack-bridging
- Perfect, simple fixation
- Tried-and-tested waterproofing for construction joints



### **Triflex Glass Primer**

### **Glass substrates**

- Can be used on virtually all glass and nanocoated surfaces
- + Low viscosity: no inconvenient runs
- No abrasion required
- + Fast drying and fast recoat time



### Triflex Special Fleece moulded components

### **Standard joints**

- Simple, compliant waterproofing of penetrations, gullies, inner and outer corners as well as pipe ducts
- + Reduction of cutting work
- + Reduction of application times
- Clean finishing of details and appealing look



### Simple and ideal for refurbishments Triflex ProDetail for roofs.

1

**K2.** Suitable for higher quality roof structures as per DIN 18531 and the German Flat Roof Guidelines.

Checked. Certified. Field-tested.

TRIFLEX QUALITY



- Simple application even on vertical surfaces
- Approved in the application categories
   K1 (standard requirements) and
   K2 (increased requirements) as per DIN 18531
- Satisfies European tests with an external fire load of B<sub>ROOF</sub> (t1, t2, t3)
- Maximum loading level P4: reliable waterproofing of even soft roofing membranes and thermally insulated surfaces
- + Hail impact test as per DIN EN 13583
- Replaces complex structures such as apron plates on metal roofs















#### Application examples:

- *Skylights and roof surface*
- 2 Metal roof penetration
- . 3 Copper moulding
- *4* Ventilator penetration
- 5 Flat roof
- 6 Pipe duct details
- Drainage channel transition on metal roof
- 8 Green roof landscape

Tried-and-tested and robust

### Triflex ProDetail for balconies and multi-storey car parks.

### **Fire safety as per DIN 13501-1.** Triflex ProDetail is also available as an **S1-Variant**!

#### Strengths

- Can be applied on any substrate geometry
- + Simple refurbishment in the joint area
- Heat resistant up to +250 °C for use under mastic asphalt
- Application without a flame on wooden frames and plastic sections
- Can withstand high mechanical loads, also suitable for roll overs
- + Can be simply recoated even after extended periods
- Can be used on mastic asphalt



### Dynamic crack-bridging Triflex ProDetail for joints.

### Strengths

- Exceptional flexibility and loading capacity
- + Expansion joint formation for green areas and areas for pedestrians and vehicle traffic
- Tested for waterproof concrete joints as per the testing principles "Junctions of structural waterproofing on concrete components with high water penetration resistance" (PG-ÜBB)
- Suitable for waterproofing in connection with joint tapes
- Heat resistant up to +250 °C for use as splash water protection under mastic asphalt



Extremely strong and wear resistant

### Triflex ProDetail from foundations to feed passages.

#### Strengths

- Chemically resistant to liquid manure, slurry, silage effluent and much more
- + Compensation of movement in the transition from the base to the foundation
- Impermeable thanks to full-surface adhesion to the substrate
- Extremely flexible system even in areas in contact with soil
- + Hydrolysis and alkali resistant





### Triflex project expertise

As a manufacturer and direct distributor of liquid applied waterproofing for roofs, balconies, multistorey car parks and much more, we have almost 40 years of project experience and always offer customised solutions to meet your requirements. We ensure ideal cooperation between contractors, planners, our staff and systems. The channels are short and direct, and personal contact is guaranteed without complications. Welcome to the Triflex family.



#### Triflex training expertise

We communicate our know-how directly and bypass trade intermediaries: we train and provide advice before, during and after the project. This guarantees the best possible application results, optimal solutions and long-term satisfaction.

MORE THAN JUST DETAIL WATERPROOFING.

	ALCONTROLLED.
	ZERTIFIKAT
	()
	Triffex
14	"Handle Children and the
TT	40 20

### Triflex quality

- Highest possible categories as per the European Technical Approvals (ETAG 005).
- Certified safety as per ETA, root- and rhizome-resistant as per FLL.
- Material guarantee filed with the Central Organisation of the German Roofing Trade Association (ZVDH).
- Continuous internal and external quality controls as well as enhancement and optimisation of products.

### **Triflex service**

This is where we as a manufacturer and direct distributor are closer to the action: we support and supervise your project with our technical advisers and applications engineers.

We deliver to the construction site on schedule, offer advice from the word go, help you with offers and use our technical expertise to assist with execution and, in doing so, guarantee the long-term success of your project.

## Triflex ProDetail **Reference projects.**



#### Planetarium, Hamburg (DE)

- Component: Water tankProject size:
- 110 m<sup>2</sup> spillways, 250 m<sup>2</sup> tank edge
- Completion: 2011



#### La Géode, Paris (FR)

- Component: Water tank
- Project size: 1,800 m<sup>2</sup>
- Completion: 2014



#### Troja Bridge, Prague (CZ)

- Component:
   Steel rod anchoring
- Project size: 530 m<sup>2</sup>
- Completion: 2014



#### Pergamonmuseum, Berlin (DE)

- Component: Glass roof
- Project size: 1,800 m
- Completion: 2004



#### Forwarding company Nosta, Piding (DE)

- Component: Solar roof
- Project size: 25,000 m<sup>2</sup>
- Completion: 2009



#### Underground carpark Karlsbau, Freiburg (DE)

- Component:
   Intermediate deck
- Project size: 5,000 m<sup>2</sup>
- Completion: 2012

### Compatible with all substrates.

Substrate	without primer	with primer
Asphalt		•
Concrete		•
FRP / Skylight frame		••••••
Glass		•
Hot bitumen coating/cold bitumen coating	•••••••	
Metals (stainless steel, copper, zinc, etc.)	0	••••••
Plastic sheeting (EVA)		••••••
Plastic sheeting (FPO/TPO)		
Plastic sheeting (PIB)	0	••••••
Plastic sheeting (PVC-P, nB)	•	
Polymer bitumen sheeting (PY-E) mod. (SBS)	•	••••••
Polymer bitumen sheeting (PY-E) mod. (APP)		
PU mouldings and rigid foam boards	•	•••••••
PVC mouldings	•	•••••••
Rubber sheeting (EPDM)		•
	•••••••	







International

Triflex GmbH & Co. KG Karlstrasse 59 32423 Minden | Germany Fon +49 571 38780-708 international@triflex.com www.triflex.com