

Gutter profile

Triflex Framebox



Product information

Applications



The Triflex Framebox drainage channel is used in barrier-free door sills and on all surfaces with a gradient to ensure smooth drainage. Triflex Framebox is to be used in combination with the Triflex BIS system and the products Triflex Ceryl Level 215+ and Triflex CeFix Screed 631.

Properties

Triflex Framebox is a nested gutter made of galvanised steel and can therefore be used flexibly on site.

Pack size

For dimensions see sketch:



Profile width:

15.5 cm or 13 cm respectively as Type B (wide) or Type S (narrow).

Profile length: 50 or 100 cm

System accessories:

Height adjuster, ACO Frameline, DN 40 drain socket, ACO grating (mesh grating, grating with longitudinal bars)

Conditions for use

The Triflex Framebox is extended to the required width on site. A cut-out is only necessary as soon as an outer or inner corner has to be created.

For smooth drainage, install a gradient in the direction of the drain socket.



General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for the respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.