

Adhesive

# Triflex TecGrip 620



## Product information

### Applications

Triflex TecGrip 620 is used as a bonding agent on Triflex SmartTec sealants. This product can be used to pre-treat SmartTec layers to material that is 24 hours old and up to 100 days old. It should be checked on site whether pre-treatment on older surfaces is possible. Once the bonding agent has dried, it can be connected with Triflex SmartTec.

### Properties

Triflex TecGrip 620 offers the following features:

- 1-component
- Easy to use
- Fast-curing

### Pack sizes

Plastic bottle

0.50 l Triflex TecGrip 620

### Colours

Orange-brown

### Storage

Can be stored unopened for approx. 6 months in a cool, dry place above freezing. Store at temperatures between +10 °C and +30 °C. Keep out of direct sunlight when in storage and on the construction site.

### Conditions for use

Triflex TecGrip 620 can be applied at substrate and ambient temperatures between +5 °C and +30 °C.

### Preparation of the substrate

The area to be treated must be free of loose or adhesion-reducing particles.

### Mixing instructions

The product can be applied immediately after the container has been opened.

### Application instructions

The bonding agent is applied by rolling it onto the surface where it forms a film. For vertical surfaces, the material must be applied in two work steps. Due to the intrinsic colour, it's important to ensure that the masking tape is placed as accurately as possible, especially with light background colours.



### Material consumption

Approx. 0.10 l/m<sup>2</sup> on a smooth, even surface

### Drying time

Approx. 25 mins. at +20 °C

### Information on particular hazards

See Safety Data Sheet, section 2

### Safety advice

See Safety Data Sheet, sections 7 and 8

### Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

### General information

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the wide variety of on-site requirements and conditions, the user is required to test the product's suitability for the particular purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.