# Special aggregate Triflex Stone Design S

# **Product information**

# **Applications**

Triflex Stone Design S is used to create the surface variant Triflex Stone Design.

# **Properties**

High-quality, colorfast and naturally quarried special aggregates without coloring.

- Type A: marble gravel, grain size 1–4 mm
- Type C: granite gravel, grain size 1–4 mm
   Type C: granite gravel, grain size 2–4 mm
- Type C: granite gravel, grain size 2–4 mi

# Pack size

# Sack

25.00 kg Triflex Stone Design S

#### Colours

Type A: marble gravel, grain size 1-4 mm:

finish and details
per 02
per 02
te 04
rtz 01
y 01
e 02

Type C: granite gravel, grain size 2-4 mm:

Colour of Triflex Stone Design S	Colour for finish and details
GS153 Tuscany	2053 Amber 02
GS753 Iceland	7043 Slate 03
GS853 Brittany	3091 Ruby 04

The recommended substrate colour is created with Triflex Cryl Finish 205.

#### Storage

Store in a cool, dry place above freezing.

### **Conditions for use**

See Triflex Stone Design R 1K product information.



# Preparation of the substrate

The substrate must be sound, dry and free of loose or adhesion-reducing particles. Possible unevenness of the surface must be smoothed out. Ensure that the surface has a minimum gradient of 2 % and avoid standing water. Ensure that structural measures are taken to prevent moisture penetration from underneath. Substrate adhesion must be tested on a case-by-case basis.

# Mixing instructions

The Triflex Stone Design S special aggregate must be dry and free of residual moisture before starting the mixing process. The stones are mixed with the binder Triflex Stone Design R 1K.

See Triflex Stone Design R 1K product information.

#### . . . . . .

Important note:

Triflex Stone Design S is a natural product. There may be colour variations between individual sacks. The sacks must be checked and, if necessary, mixed with one another before use on the construction site.

# **Material consumption**

On a smooth, even surface at a layer thickness of approx. 8 mm:

		Type C: granite gravel,
	grain size 1–4 mm	grain size 2–4 mm
Triflex Stone Design R 1K	0.80 kg/m²	0.80 kg/m <sup>2</sup>
Triflex Stone Design S	14.40 kg/m <sup>2</sup>	14.40 kg/m²

## **General notes**

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.

