



Product information

Product description

Triflex Line EasyTherm is a prefabricated thermoplastic marking in accordance with RMS and StVO for heavily used traffic areas in urban and interurban areas. Application takes place in a few steps without machine technology. The prefabricated lines and symbols are fused with the substrate using a propane burner. Triflex Line EasyTherm is based on hydrocarbon resins, which prevents discolouration and the release of hazardous substances containing carbon. The selected raw materials and the organic colour pigments are free of heavy metal. As a result, marking does not fall within the scope of the REACH Regulation.

Applications

Triflex Line EasyTherm is used as type I and type II marking in urban and interurban areas. The great variety and individual design options also allow application in car parks, company premises, playgrounds or school playgrounds.

Properties

The prefabricated thermoplastic marking offers the following features:

- Quick application
- Easy to apply
- High level of whiteness
- High retroreflection thanks to 30 % premix glass beads
- Non-slip finish thanks to special drop-on material
- Can be driven over after a few minutes
- Resistant to petrol, oil, de-icing salt and frost

Pack sizes

Motif in cardboard packaging incl. installation instructions

Colours

9016 Traffic white

Other colours on request.

Storage

Can be stored flat for approx. 24 months in a cool, dry place above freezing. Store at constant temperatures, away from direct sunlight in storage and on the construction site.



Conditions for use

Triflex Line EasyTherm can be applied at substrate temperatures of at least +5 °C.

Preparation of the substrate

The substrate must be sound, dry and free of ice, loose particles, grease and oil.

Application instructions

Activating the substrate:

Heat the substrate with a torch to remove any residual moisture.

Triflex Than Primer L 1K:

use Triflex Than Primer L 1K for adhesion between concrete substrates and Triflex Line EasyTherm, and then allow to dry completely.

Triflex Line EasyTherm:

Lay the motif on the previously primed surface according to the installation instructions. Heat evenly with a torch at a distance of 10 to 30 cm at a temperature between 200 °C and 220 °C until the marking has completely fused with and bonded to the substrate.



Product information

Product overview

Lines and blocks

Article no.	Article	Packaging	Colour	Storage
26983-010-1	Triflex Line EasyTherm, line 100 x 12 cm	25	9016 Traffic white	■
26983-010-2	Triflex Line EasyTherm, line 100 x 25 cm	10	9016 Traffic white	■
26983-010-3	Triflex Line EasyTherm, line 100 x 50 cm	5	9016 Traffic white	■
26983-010-4	Triflex Line EasyTherm, line 50 x 12 cm	50	9016 Traffic white	■
26983-010-5	Triflex Line EasyTherm, block 50 x 50 cm	10	9016 Traffic white	■

Direction arrows

Article no.	Article	Packaging	Colour	Storage
26983-011-1	Triflex Line EasyTherm, straight arrow 500 cm	2	9016 Traffic white	■
26983-011-2	Triflex Line EasyTherm, arrow right 500 cm	2	9016 Traffic white	■
26983-011-3	Triflex Line EasyTherm, arrow left 500 cm	2	9016 Traffic white	■
26983-012-2	Triflex Line EasyTherm, additional arrow right 500 cm	2	9016 Traffic white	■
26983-013-2	Triflex Line EasyTherm, additional arrow left 500 cm	2	9016 Traffic white	■
26983-013-1	Triflex Line EasyTherm, turn arrow right 500 cm	2	9016 Traffic white	■
26983-012-1	Triflex Line EasyTherm, turn arrow left 500 cm	2	9016 Traffic white	■
26983-014	Triflex Line EasyTherm, advance notice arrow 500 cm	2	9016 Traffic white	■

Numbers and letters

Article no.	Article	Packaging	Colour	Storage
26983-019	Triflex Line EasyTherm, "30" 400 cm	1	9016 Traffic white	■
26983-020	Triflex Line EasyTherm, "BUS" 400 cm	1	9016 Traffic white	■

Symbols and pictograms

Article no.	Article	Packaging	Colour	Storage
26983-015-3	Triflex Line EasyTherm, cyclists 90 x 80 cm	1	9016 Traffic white	■
26983-015-1		5	9016 Traffic white	■
26983-015-4	Triflex Line EasyTherm, cyclists 130 x 100 cm	1	9016 Traffic white	■
26983-015-2		5	9016 Traffic white	■
26983-016-3	Triflex Line EasyTherm, wheelchair user 100 x 70 cm	1	9016 Traffic white	■
26983-016-2		5	9016 Traffic white	■
26983-021-2	Triflex Line EasyTherm, children (crossing from the right) from traffic markings 136-10 100 x 52.5 cm	1	9016 Traffic white	■
26983-021-1		5	9016 Traffic white	■
26983-018	Triflex Line EasyTherm, electric charging point 130 x 100 cm	1	9016 Traffic white	■