

Primer

Triflex CeFix Primer 795



Product information

Applications

Triflex CeFix Primer 795 is used as an adhesive primer on mineral substrates (screed/concrete) in conjunction with Triflex CeFix Screed 631.

Properties

Triflex CeFix Primer 795 is a 1-component solvent-free polymer dispersion which is characterised by its ease of use.

Pack size

Plastic canister

5.00 kg Triflex CeFix Primer 795

Colours

Transparent

Storage

Can be stored unopened and unmixed for approx. 6 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.

Conditions for use

Triflex CeFix Primer 795 can be applied at substrate and ambient temperatures of min. +7°C to max. +35°C. Can also be used for interiors. During the curing process, the temperature must not drop below the minimum application temperature.

Preparation of the substrate

The substrate must be prepared by milling or shot-blasting until it is sound, dry and free of loose or adhesion-reducing particles. Ensure that moisture cannot penetrate from underneath. Substrate adhesion must be tested on a case-by-case basis. Minimum tensile adhesion strength: 1.5 N/mm².

Use on asphalt is not permitted. For use on resin-modified mortars, an on-site compatibility test must be carried out.

During application, the surface temperature must be at least 7°C above dew point. Below that, a separating film of moisture can form on the surface to be worked on (DIN 4108-5, table 1). See dew point temperature table.



Mixing instructions

Triflex CeFix Primer 795 is diluted with water with a mixing ratio of 1:3.

It is not necessary to add a catalyst.

Mixing ratio

1.00 kg	Triflex CeFix Primer 795
3.00 kg	Water
4.00 kg	

Methods of application

Apply Triflex CeFix Primer 795 with a broad brush or a universal roller.

Material consumption

Min. 0.30 kg/m²

Primer

Triflex CeFix Primer 795



Product information

Notes on special hazards

See safety data sheet, section 2

Safety tips

See safety data sheet, sections 7 and 8

Measures in case of fire or accidents

See safety data sheet, sections 4, 5 and 6

General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the wide variety of on-site requirements and conditions, the user is required to test the product's suitability for the particular purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.