

Adhesive

Triflex ProDrain Fix



Product information

Applications

Triflex ProDrain Fix is used to bond the Triflex DC-MAT Uncoupling Membrane to the Triflex ProDrain system.

Properties

The adhesive offers the following features:

- High adhesive strength
- Very easy to use
- Good stability
- Malleable
- Flexible

Pack sizes

Paper sack

25.00 kg Triflex ProDrain Fix

Storage

Store in a cool, dry, frost-free place and keep protected from moisture.

Conditions for use

Substrates must be sound, even, clean and free from adhesion-reducing residues.

Preparation of the substrate

See the system description for Triflex ProDrain.

Mixing instructions

Mix with water using a mixing machine until there are no more lumps. Make sure that you only mix the amount of adhesive that can be used throughout. You should not wait too long between applications.

Mixing ratio

Mix 25.00 kg of Triflex ProDrain Fix with 7.50 l of water.



Application instructions

Apply the adhesive in 2 coats. The first layer is applied thinly in sections and in the entire membrane with the smoothing trowel. The second coat is applied on top of the still fresh coat with a notched trowel. Only apply as much adhesive as can be covered with the Triflex Uncoupling Membrane DC-Mat before a skin is formed. Press the uncoupling membrane into the adhesive bed with a pressure roller.

During the application and drying of Triflex ProDrain Fix, the substrate temperature must not drop below +5 °C. Do not use in direct sunlight. Be aware that in windy conditions, shorter setting times are sufficient.

Important:

The Triflex Uncoupling Membrane DC-Mat must be loaded as little as possible when applying the load distribution layer and the subsequent Triflex BTS-P system. To protect it from point loads, a thin wooden board can be placed on top.

Material consumption

Approx. 3.00 kg/m² – depending on the selected notching of the notched trowel

Pot life

Approx. 1 hr. at +20 °C

Adhesive

Triflex ProDrain Fix



Product information

Information on particular hazards

See Safety Data Sheet, section 2

Safety advice

See Safety Data Sheet, sections 7 and 8

Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

General information

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the wide variety of on-site requirements and conditions, the user is required to test the product's suitability for the particular purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.