

Primer

Triflex Than Primer 533



Product information

Applications

Triflex Than Primer 533 is used as a primer on PVC substrates for Triflex SmartTec products.

Properties

Triflex Than Primer 533 is a 1-component, solvent-containing primer with a polyurethane base for Triflex SmartTec products. Triflex Than Primer 533 offers the following features:

- Fast-drying
- Fast recoat time
- Liquid form

Pack size

Metal canister

0.40 litres Triflex Than Primer 533

Colours

Brownish

Storage

Can be stored unopened for approx. 12 months in a cool, dry place above freezing. Keep the container out of direct sunlight, even on the construction site.

Conditions for use

Triflex Than Primer 533 can be applied at substrate and ambient temperatures of between +10°C and +35°C.

Preparation of the substrate

The substrate must be sound, dry and free of ice, loose and/or adhesion-reducing particles, grease and oil. Substrate adhesion must be tested on a case-by-case basis.



Material consumption

Approx. 100 ml/m² on a smooth, even surface

Drying time

Can be recoated after: approx. 20 mins. to max. 12 hrs at +20°C

Notes on special hazards

See Safety Data Sheet, section 2

Safety tips

See Safety Data Sheet, sections 7 and 8

Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

General notes

We guarantee the consistently high quality of our products. Non-system substances must not be added to Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.