

Universal cleaner

Triflex Cleaner



Product information

Applications

Triflex Cleaner is used with all Triflex PMMA, EP, PU and PUA products. It is used to pre-treat substrates and to degrease metal when overcoating or if work is interrupted. In addition, soiled tools can be cleaned with Triflex Cleaner.

Properties

Solvent-based universal cleaning agent

Pack size

Can

1.00 l Triflex Cleaner

Canister

9.00 l Triflex Cleaner

27.00 l Triflex Cleaner

Colours

Transparent

Storage

Can be stored unopened for approx. 12 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.

Instructions for use

Clean tools with Triflex Cleaner immediately after use. Merely placing tools in the cleaner will not prevent hardening.

If Triflex waterproofing and coating work is interrupted for more than 12 hours, the transition must be moistened with Triflex Cleaner.

In the case of overcoating, the cleaner must be aired for approx. 20 to 25 min.



Material consumption

Depending on the degree of soiling and the type of substrate, allow a volume of at least 0.20 l/m².

Notes on special hazards

See Safety Data Sheet, section 2

Safety tips

See Safety Data Sheet, sections 7 and 8

Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.